



24 Volt Power Adapter for NMEA2000® Part No 3890



- **17 - 32 Volt system input**
- **13.6 Volt NMEA2000® output**
- **6 Amp Output Capability**
- **Robust Aluminium Construction**
- **Easy to install**
- **2 metre power lead with single Micro plug / socket to NMEA2000 bus**

The 3890 24 Volt Power Adapter allows a standard NMEA2000® network to be powered from the yachts 24 volt supply.

The 24 Volt input can vary from 17 - 32 Volts whilst the fully stabilised unit holds the output steady.

The unit provides the NMEA2000® standard 13.6 Volts supply at up to 6 Amps which is sufficient to power any normal NMEA2000® network.

The 3890 comes with a complete mounting kit including a dedicated mounting bracket and screws and 1/4" crimp connectors for the 24 volt input connection.

It connects to the NMEA2000® network by means of a 2 metre power Tee that has the standard Micro Plug and Socket to be included in the NMEA2000® Trunk or backbone cable.

The 3890 24 Volt Power Converter is robustly constructed to the IEC60945 Maritime Navigational and Radiocommunications Equipment Standard to ensure high reliability and trouble free operation for many years.

It comes complete with 2 metre Power Tee cable, mounting bracket and screws, crimp connectors and full installation and operation instructions.

24 Volt Power Adapter for NMEA2000® Part Number 3890

Specification	
Input Voltage	17 - 32 Volts
Output Voltage	13.6 Volts
Output Current	6 Amperes
Certification	
Maritime Navigation and Radiocommunication Equipment	Tested to IEC 60945
CE Mark and FCC	Electromagnetic Compatibility
NMEA PGNs	
Periodic	None
Requested	None
Protocol	None
Electrical	
NMEA Output Voltage	13.6 Volts DC
Reverse Battery	Protected
Load Dump	Protected
Mechanical	
Size	90mm Long 88mm Wide 50mm Deep
NMEA2000 Cable Length	2 Metre with micro plug / socket
Input connection	.25" spade terminals
Weight	Approx 450 gms
Mounting	Supplied bracket
Environmental	
IEC 60954 Classification	Protected
Protection	IP40
Operating Temperature	-25C to +55C
Storage Temperature	-40C to +70C
Relative Humidity	93%RH@40C per IEC60945-8.2
Electromagnetic Emission	Conducted and Radiated as per IEC 60945-9
Electromagnetic Immunity	Conducted, Radiated, Supply and ESD per IEC 60945-10



The inclusion of any vessels in any picture does not infer that their manufacturer endorses this product. Our policy is one of continuous product improvement so product specifications are subject to change without notice. Our products are designed to be accurate and reliable, however, they should only be used as aids to the safe management of the boat and not as a replacement for traditional aids and techniques.

Copyright © 2008 Offshore Systems (UK) Ltd. All rights reserved.

Offshore Systems (UK) Ltd
Unit 11 Milton Business Centre, Wick Drive,
New Milton, Hampshire, BH25 6RH, United Kingdom
Tel: +44(0)1425 610022 Fax: +44(0)1425 614794
Email: mail@osukl.com Web: www.osukl.com